

ACCESS CONTROL



1812-Access Plus Surface Mount Stainless (1812-090)

Telephone Entry System



The 1812 Access Plus is a control and communication system for residential applications. The 1812 Access Plus is PC Programmable and IP Addressable. Each Access Plus Series unit allows Voice and Data connection over either Cellular, VoIP, Wireless, or POTS. DKS offers easy ways to connect fast using the DKS IM Server and DKS Cellular services. With the easy to use Access Plus Account Manager programming software, you can customize the system immediately. The 1812 Access Plus controls a main door or gate and can easily be expanded to control up to six additional access points. The 1812 Access Plus features an upgraded processor, a new high fidelity digital voice circuit, better volume control, a lighted push-button and additional call out telephone

numbers (up to 27). Discerning homeowners will appreciate the additional programming, reporting and advanced features found in the 1812 Access Plus system.

DoorKing's Access Plus Account Manager Software is a powerful, flexible and easy to use computer program that allows you to manage access control in a variety of controlled access applications.

Features:

- IP addressable – program from your PC via LAN/WAN or an internet connection or via built-in modem
- Access Plus Account Manager programming software included
- Add up to six (6) card readers, keypads or RF receivers (RS-485)
- 100 card / transmitter / keypad codes (50 with phone numbers; 50 access codes only)
- Up to 30 holidays can be added to access and hold open time zones
- Control access points from your PC. Schedule lock and unlock times, lock or unlock an access point with the click of your mouse
- 10 temporary access codes with start and end dates
- 500 event transaction buffer
- Email notification of events of your choice. Internet connection required
- Call waiting
- Call forwarding with time zone restrictions
- Unique double ring
- Built-in clock / calendar
- Do-not-disturb feature
- Four "hold open" time zones
- Answer machine bypass feature
- 50 5-digit entry codes with time zone restrictions on some codes
- 10 Temporary entry codes with start and end dates
- Intercom mode for use with PBX and KSU phone systems
- Camera ready

Specifications:

- Hands free, full duplex digital audio circuit.
- Interfaces with a single phone line
- 27 dial-out phone numbers
- Two relays for door or gate control
- Ability to control an additional six (6) access points with card readers, keypads or RF controls
- Programming Method: System keypad, touch-tone telephone, or from PC
- 16 VAC, 20 VA (250 ma) power transformer provided
- FCC (US): DUF6VT-12874-OT-0
- DOC (CAN): 1736 4507 A
- Complies with UL 294; ETL Listed
- Surface mount dimensions: 6.13"H x 10"W x 5.25"D